

AIS 0206 CYCLONE

PRODUCT DETAILS

PRODUCT DETAILS | FEATURES | SPECIFICATIONS |
WARRANTY INFORMATION



C. (217) 335-4558

M. (+44) 7772736082

E. info@agriincinerators.com

W. www.agriincinerationsystems.com

One of the key reasons our incinerators are recognized as being '*probably the best*' on the world market, is the use of our market leading and trusted low thermal mass monolithic concrete lining which is used in all of our models.

All models in the Cyclone Range are supplied with a secondary chamber, ensuring they fully conform to many legislative bodies around the world.

AIS 0206 Cyclone

- With a large load capacity of up to 1300kg / 2867 lbs and an hourly burn rate of up to 68kg / 150 lbs, the AIS 0206 Cyclone incinerator is suited for the bio-secure disposal of a wide range of larger animal carcasses generated across the agricultural sector including but not limited to; Dairy / Beef Cattle, Pigs & Sows, Equine Cremation.
- A curved lid that is opened via a manual sliding action along a frame, gives full access to a large main burning chamber.
- The Bed of the AIS 0206 is low down and easy to load carcasses into via skid loaders and tractor buckets. The low height of the bed also makes it easy for de-ashing.
- PLC timer controls with automatic burner shut off function and fast ignition burners. One burner is in the main chamber, one additional burner is in the secondary chamber.
- Can be loaded whilst in operation maximizing the inherent thermal efficiency of our monolithic concrete lining, keeping running costs low.
- Optional Extra Features include; Stack Extension / Ash Rake / Inspection Door / USB Data Logger / Heat Exchanger / Control Panel screen size increase / Service Kits.



Image shown is of the AIS 0206 Cyclone model with optional Inspection Door



*Dependent on efficient usage and waste type. This may be subject to your local regulations. Speak to a member of our team for more information.

"Our mission is to build the most robust, fuel-efficient, cost-effective solution for the disposal of animal and animal by product waste and to continue to be the brand that is known world-wide for both quality of product and quality of customer service".

Be Assured of a Quality Product & Quality Service with AIS:

- Each machine is hand built by our team of skilled technicians in the UK and U.S.
- The reason your incinerator will last is due to the type of lining used. Our trusted monolithic casting system ensures maximum strength, reliability and a longer machine life. We are always happy to explain why our technology is far better than any other manufacturers product on the world market. Talk to us to find out more and make your own mind up.
- Behind the AIS brand is a team of experts who are always on hand to discuss any questions that you may have about incineration, so you can be assured of great service and a great product.
- But it goes beyond that, we stay with you for the life of the machine, always on hand if or when you need us. It's a people thing, it's an AIS thing.

*3 YEAR WARRANTY AS STANDARD:

The whole plant and associated equipment supplied as part of the overall installation will be covered by a *36-month or 2100 hours warranty (whichever soonest) from the date of dispatch from the manufacturing premises of Agri Incineration Systems Limited, except for any consumable item as listed below and provided that:

- a) Each defect has materialized under normal operating conditions and not due to misuse, abuse, or operational errors.
- b) An effective maintenance regime is operated which may include a Service Contract being taken up at the time of handover. This Service Contract should be provided by Agri Incineration Systems Limited or trained and authorized agents.
- c) The contract price, as detailed within the quotation or as amended by agreement of both parties, has been paid in full.

Consumable Parts (Items not covered under Warranty).

1. Primary Chamber Thermocouples
2. Secondary Chamber Thermocouples
3. Access Door seals
4. Control Panel indicator bulbs or LEDs
5. Burner electrodes and leads
6. Burner probes and leads
7. Burner Blast Tubes
8. Burner Diffuser Assemblies
9. Burner nozzles / ionization probes
10. Grate Bars
11. Mechanical damage of any sort

3 Year Warranty as standard, talk to us about a long-term Service Plan to suit you



Specifications	Unit - Metric		Unit - Imperial	
*Burn Rate	Up to kg/hr	68	Up to lbs/hr	150
Front / Top Load		Top		Top
Static Operational Dimensions (LxWxH)	m	8.5 x 2.2 x 5.0	feet/inch	27' 11" x 7' 1" x 16' 3"
External Height - Static	mm *inc. Stack	4950	feet/inch *inc. Stack	16' 3"
External Height - Static	mm *ex. Stack	2560	feet/inch *ex. Stack	8' 5"
Weight	Tonne *estimated	6.6	lbs *estimated	14551
Load Height from Ground (floor to bottom edge)	mm	500	feet/inch	1' 8"
*Fuel Consumption Diesel	LPH *est during main burn	11.8 - 17.9	GPH *est during main burn	3.1 - 4.7
*Fuel Consumption LPG	LPH *est during main burn	17 - 27	GPH *est during main burn	3.7 - 7.1
*Fuel Consumption Nat Gas	m ³ /h *est during main burn	12 - 18	ft ³ /h *est during main burn	416 - 634
Grate Bars		No		No
Load Door Opening (Width x Height/Depth)	mm *area	3100 x 1700	ft/inch *area	10' 2" x 5' 7"
Chamber Size (LxWxH)	m	3.1 x 1.7 x 1.3	ft/inch	10' 2" x 5' 7" x 4' 1"
Chamber Actual Volume	m ³	5.75	ft ³	203
Chamber Load Volume	m ³	2.36	ft ³	83
*Chamber Load Capacity	kg	1300	lbs	2867
Std Stack Diameter	inch/mm *2D Size	14"	inch/mm *2D Size	14"
No. Main Burners		1		1
No. Secondary Burners		1		1
Burner Output	kW *heat	260	Btu *heat	887,157
Electric Consumption	kW *electricity	0.25	kW *electricity	0.25

*The optimum performance of the incinerator is dependent upon efficient usage and waste type

"Our mission is to build the most robust, fuel-efficient, cost-effective solution for the disposal of animal and animal by product waste and to continue to be the brand that is known world-wide for both quality of product and quality of customer service".

Speak to a member of AIS today.

Call us on: (217) 335-4558

Email us: info@agriincinerators.com

Visit us: www.agriincinerationsystems.com